

COMANCHE GEAR



10340 REGENT CIRCLE ∞ NAPLES, FL 34109
PHONE & FAX 239/593-6944 ∞ CELL 239/404-7524
MKURKE@COMANCHEGEAR.COM

tyco / Electronics
AMP

Pressure Type Wire Connector Chart
AMP* SOLISTRAND* Terminals
and Splices (Use Type "W" Tooling)

408-2049
30 MAY 00 Rev H
TO BE SOLD ONLY WITH
INSTALLATION INSTRUCTIONS **CU**

AMP WIRE RANGE	UL 424C LISTED	SP LR 7189 CERTIFIED
22-16 Solid or Stranded	22-16 Solid or Stranded	22-16 Solid or Stranded
16-14 Solid or Stranded	16-14 Solid or Stranded	16-14 Solid or Stranded
12-10 Solid or Stranded	12-10 Stranded	12-10 Solid or Stranded
8 through 600 MCM Solid or Stranded	8 through 600 MCM Stranded	8 through 4/0 Solid or Stranded

NOTE: 22-16 terminals and splices are stamped 22-18 in accordance with MIL-T-7928.
DANGER: Not to be used on aluminum wire – may cause equipment failure leading to serious injury or death.

©2000 Tyco Electronics Corporation, Harrisburg, PA. TOOLING ASSISTANCE CENTER 1-800-722-1111 LOC B
*Trademark All International Rights Reserved. AMP FAX/PRODUCT INFO 1-800-522-6752 Revised per EC 0990-0552-00

THIS IS THE UN-INSULATED BUTT SPLICE USED IN THE NOSE GEAR PORTION OF YOUR WIRING HARNESS KIT.



THIS IS THE "TYPE W" TOOLING REFERRED TO IN THE AMP LITERATURE ABOVE WHICH IS THE SUGGESTED TOOL TO CRIMP THE BUTT SPLICES AT THE NOSE GEAR HARNESS. THIS TOOL IS AVAILABLE FOR LOAN; A VERY LIMITED QUANTITY AVAILABLE FOR PURCHASE - GOOD SERVICEABLE CONDITION - \$50, BUT THAT CAN CHANGE DEPENDING ON THE SUPPLY AND MY COST.